


## Product No: OTP25B3M

### ABB OTP25B3M ENCLOSED SWITCH DISCONNECTOR OTP25B3M

#### FEATURES

- 3 pole, Enclosed switch disconnecter
- Plastic Enclosure
- Black selector handle
- Interlocked cover, Defeatable interlocking
- Enclosure is UV protected, protected against low-pressure water jets
- Handle is padlockable and made for 3 padlocks
- The switch is made for 5 wire system and have a fixed neutral terminal and PE terminal
- Degree of protection: IP65



#### General Information

Brand	ABB
Product Type	Enclosed
Suitable For	Distribution Board Installation
Type	Main Switch

#### Technical Attributes

Conventional Thermal Current - I <sub>the</sub> (A)	32
Maximum Operational Voltage AC (V)	750
No. of Poles	3
Power Loss (W)	0.6/Pole
Rated Impulse Withstand Voltage (kV)	0.5
Rated Insulation Voltage (V)	750
Rated Operational Current AC-21A 415V (A)	25
Rated Operational Current AC-22A 380-415V (A)	25
Rated Operational Current AC-22A 690V (A)	25
Rated Operational Current AC-23A 380-415V (A)	20
Rated Operational Current AC-23A 500V (A)	20
Rated Operational Current AC-23A 690V (A)	11
Rated Operational Power AC-23A 380-415V (kW)	9
Rated Operational Power AC-23A 500V (kW)	9
Rated Operational Power AC-23A 690V (kW)	9

### Technical Attributes

Rated Operational Voltage (V)	750
Rated Short-Time Withstand Current - I <sub>cw</sub> (kA)	0.5
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	0.5
Rated Uninterrupted Current - I <sub>u</sub> (A)	32

### Physical Attributes

Control Element Colour	Black
Enclosure Material	Plastic
Handle Colour	Black
Handle Type	Selector
Included	Handle

### Dimensions

Cable Cross Section (mm <sup>2</sup> )	0.75 - 10
Dimensions (mm)	130W x 150H x 60D

### Protection & Standards

Degree of Protection	IP65
NEMA Degree of Protection	1
Pollution Degree	3
Rated Impact Resistance	Housing IK08
Standards and Approvals	IEC 60947-1, IEC 60947-3

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------