

Product No: 591D049E5G01100112000

BD SENSORS DMK457 PRESS. T/M F OR SHIPBUILDING AND OFFSHORE DMK457 PRESS. T/M FOR SHIPBUIL 591D049E5G01100112000

FEATURES

- Pressure port in CuNiFe (sea water resistant).
- Ideal for oxygen applications.
- LR, DNV, ABS & CCS certified.



| General Information | |
|-------------------------------|-------------------------------------|
| Brand | BD SENSORS |
| Product Series Product Series | DMK 457 |
| Product Type | Ceramic Sensor |
| Suitable For | Fuel and Oil Water and Sea Water |
| Version | Standard |

| Technical Attributes | |
|-----------------------|--|
| Accuracy | 0.5 % FSO |
| Application | Drives, Compressors, Boiler, Pneumatic Control Systems, Oxygen applications |
| Electrical Connection | Male and female plug ISO 4400 GL (for cable Ø 4.511 mm) [Cable socket is GL-approbated] |
| Electrical Protection | Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326, DNV (Det Norske Veritas). |
| Input Pressure (bar) | 0.81.4 |
| Mechanical Connection | G1/2" DIN 3852 |
| Mechanical Stability | 4 g (according to DNV: class B, curve 2 / basis: IEC 60068-2-6) |
| Operational Life | 100 million load cycles. |
| Output Signal | Intrinsic safety 4 20 mA / 2-wire |



| | Storage: -40 100 °C |
|--------------------|-------------------------------|
| Pressure Port | Stainless steel 1.4404 (316L) |
| Response Time (ms) | < 10 |
| Seals | FKM |

| Physical Attributes | |
|---------------------|---------------------|
| Diaphragm Material | Ceramics Al2O3 96 % |

| Resources | |
|------------------------------|--------------------|
| Product catalogue (Flipbook) | Download from here |