

Product No: HS5L-XG7Y4M-G

IDEC INTERLOCK 2 CONTACTS SOLENOID LOCKSAFETY_SWITCH HS5L-XG7Y4M-G

FEATURES

- 1400N Locking Strength
- Gold-plated contacts suitable for small loads
- The head orientation can be rotated
- allowing 8 different actuator entries
- Applicable Standards: EN ISO14119
- GS-ET-19 (TUV approval)
- EN60947-5-1 (TUV approval)
- UL508 (UL Listing)
- CSA C22.2 No. 14 (c-UL listed)
- IEC 60204-1/EN60204-1



General Information

| | |
|--------------|-------------------------|
| Brand | IDEC |
| Product Type | Safety Interlock Switch |

Technical Attributes

| | |
|---------------------------------|---------|
| Contacts | 2 |
| Minimum Electrical Life | 100000 |
| Minimum Mechanical Life | 2000000 |
| Rated Insulation Voltage (V) | 250 |
| Rated Thermal Current - Ith (A) | 2.5 |

Physical Attributes

| | |
|------------------------------------|-----------|
| Operational Temperature Range (°C) | -25 to 55 |
|------------------------------------|-----------|

Dimensions

| | |
|-----------------|------------------|
| Dimensions (mm) | 35W x 40H x 127D |
| Weight (g) | 300 |

Protection & Standards

| | |
|----------------------|------|
| Degree of Protection | IP67 |
|----------------------|------|

Pollution Degree

3

Resources

Product catalogue (Flipbook)

[Download from here](#)