


## Product No: MC2C310ATD

### ABB MC2C310ATD MINI CONTACTOR 24 V DC - 3 NO - 0 NC - SCREW TERMINALS MC2C310ATD

#### FEATURES

- Compact design, ideal for installations with limited space
- Ideal for residential, commercial, and industrial use
- Auxiliary functionality
- Options for wall or rail mounting to accommodate different installations needs



#### General Information

Brand	ABB
Product Type	Mini Contactor
Series	M

#### Technical Attributes

Actuating Voltage Type	DC
Auxiliary Contacts	1NO
Main Circuit Electrical Connection	Screw Connection
Mode of Operation	DC
No. of Normally-open Auxiliary Contacts	1
No. of Normally-open Contacts	3
No. of Poles	3
Operating Voltage AC (V)	440
Power Loss (W)	0.7/pole AC-1
Rated Control Circuit Voltage DC (V)	24
Rated Control Supply Voltage AC (V)	24
Rated Control Supply Voltage DC (V)	24
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	750
Rated Operational Current AC-1 400V (A)	20

Rated Operational Power AC-3 400V (kW)	5.5
Rated Operational Voltage AC (V)	440
Rated Supply Voltage AC (V)	24
Terminal Type	Screw

#### Physical Attributes

Mounting Type	DIN Rail / Wall
Operational Temperature Range (°C)	-40 to +55

#### Dimensions

Dimensions (mm)	45W x 48H x 68D
-----------------	-----------------

#### Protection & Standards

Degree of Protection	IP20
----------------------	------

#### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------