

## Product No: ISDA073496R1

### ABB E2.2N/MS 2000 3P WMP ISDA073496R1

#### FEATURES

- IP30 protection for fixed parts
- Lifting plates
- Adjustable rear terminals
- Racked-out mechanism lock, anti-insertion lock, standard shutter lock
- Lever for racking in/out
- S51 250V trip indicator



#### General Information

Brand	ABB
EAN	8015644773465
Product Type	Non-automatic ACB
Suitable For	Distribution Board Installation
Type	Main Switch
Version	Withdrawable

#### Technical Attributes

Design of Control Element	Push Button
Current Type	AC
Main Circuit Electrical Connection	Bolt Connection
Maximum Operational Voltage AC (V)	690
No. of Poles	3
Power Loss (W)	450
Rated Current (A)	2000
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Current AC-21A 415V (A)	2000
Rated Operational Current AC-23A 380-415V (A)	2000
Rated Operational Voltage (V)	690
Rated Short-Time Withstand Current - I <sub>cw</sub> (kA)	66

Rated Short-time Withstand Current - I <sub>cw</sub> (kA/1s)	66
Rated Short-time Withstand Current - I <sub>cw</sub> (kA/3s)	50
Rated Uninterrupted Current - I <sub>u</sub> (A)	2000
Rated Voltage (V)	690

#### Physical Attributes

Interlockable	Yes
---------------	-----

#### Dimensions

Dimensions (mm)	317W x 425H x 383D
-----------------	--------------------

#### Protection & Standards

Degree of Protection	IP30
----------------------	------

#### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------