

ABB DS201MC10APR30 RCBO 10kA 1P+N 10A C CURVE TYPE APR 30mA

DS201MC10APR30

FEATURES

- Protection against short circuit, thermal overload and earth leakage
- Contact Position Indication (CPI)
- Earth fault indicator to identify easier earth faults
- Test pushbutton to verify the correct functioning of the device
- Laser printed data for quick identification
- Finger safety with IP20 terminals
- Pole configuration 1P+N



GENERAL INFORMATION	
Brand	ABB
Product Type	RCBO
Series	DS201MC

TECHNICAL ATTRIBUTES	
Application	Commercial and Industrial
Breaking Capacity 230V AC - Icu (kA)	15
Curve Type	C Curve
No. of Poles	1P+N
Power Loss (W)	1.8
Rated Conditional Short-Circuit Current - Inc (kA)	15
Rated Current (A)	10
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230/240
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	10
Rated Voltage AC (V)	230
Test Voltage (kV)	0.17-0.264
Type of Residual Current	APR



PHYSICAL ATTRIBUTES	
Housing Material	Insulation Group I - II, RAL 7035
Mounting Type	DIN Rail
PROTECTION & STANDARDS	
Degree of Protection	IP40 (Housing), IP20 (Terminals)
Pollution Degree	2
RESOURCES	
Product catalogue (Flipbook)	Download from here