

## Product No:159788

STAHL 9143/10-114-200-10S EX I POWER SUPPLY EX I FIELD CIRCUIT IS PAC 159788

## FEATURES

- Single-channel safety barriers with electronic current limiting
- Number of channels: 1
- Power supply: Uncontrolled 23 27 V DC
- Maximum output current: Imax 40 mA
- Operating temperature range: -20 °C to +60 °C
- IP ratings: IP40 overall, IP20 at terminals
- Suitable for installation in Zone 2, Division 2 hazardous areas
- Designed for supplying field devices with intrinsically safe auxiliary power
- Flexible and space-saving design for easy DIN rail installation

## **General Information**

Brand	STAHL
Series	9143

Technical Attributes	
Nominal Power (W)	4.6
Rated Maximum Operational Voltage AC (V)	28
Rated Maximum Operational Voltage DC (V)	35
Rated Minimum Operational Voltage AC (V)	20
Rated Minimum Operational Voltage DC (V)	18

Physical Attributes	
Maximum Temperature (°C)	70
Minimum Temperature (°C)	-20
Mounting Type	DIN Rail

Protection & Standards	
Degree of Protection	IP30

IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA SAFETY BARRIERS > IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA INTRINSICALLY SAFE ISOLATORS



Standards and Approvals

ATEX/IECeX

Resources

Product catalogue (Flipbook)

Download from here