

Product No: S304PC8

ABB MCB 4P 8A 15KA C CURVE S300P S304PC8



General Information

Brand	ABB
Product Type	MCB
Series	S300P

Technical Attributes

Power Supply Connection	Arbitrary
Curve Type	C
Dielectric Test Voltage (kV)	2
Electrical Endurance (Cycles)	20000
Maximum Operational Voltage AC (V)	457
Mechanical Endurance (Cycles)	20000
Net Weight (kg)	0.496
No. of Poles	4P
No. of Protected Poles	4P
Overvoltage Category	IV
Power Loss (W)	6.4
Rated Current (A)	8
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Operational Voltage AC (V)	415
Rated Short-Circuit Capacity - I _{cn} (kA)	25 (400V)

Terminal Type	Screw Terminals
Tightening Torque (Nm)	2.8
Voltage Type	AC/DC
Wire Stripping Length (mm)	14

Physical Attributes

Actuator Material	Insulation Group II, Black, Sealable
Ambient Temperature Range (°C)	-40 to +70 (Operation)
Housing Material	Insulation Group I, RAL 7039
Mounting Position	Any
Mounting Type	DIN Rail

Dimensions

Dimensions (mm)	70W x 88H x 69D
-----------------	-----------------

Protection & Standards

Degree of Protection	IP20, IP40 in enclosure with cover
Pollution Degree	3
Standards	CSA 22.2 No. 235, IEC/EN 60898-1, IEC/EN 60947-2, UL 1077