


PRODUCT-DETAILS

OVR T2 3N 80-440s P TS QS

OVR T2 3N 80-440s P TS QS Surge Protective Device



General Information

Extended Product Type	OVR T2 3N 80-440s P TS QS
Product ID	2CTB815708R3700
EAN	3660308525581
Catalog Description	OVR T2 3N 80-440s P TS QS Surge Protective Device

Long Description

Surge protective devices SPD type 2 protect low-voltage consumer systems against surge voltages as they are tested as SPD type 2 according to IEC 61643-11. The devices are compatible with the System pro M compact series. The SPD with "TS" are optionally equipped with a auxiliary contact. The variants with "reserve varistor" (s) offer additional protection for the system, as the SPD is not completely disconnected from the mains at the end of its service life, but with an additional smaller varistor still guarantees basic protection and the system thus until the surge arrester is replaced is still protected

Technical

Standards	IEC 61643-11 / EN 61643-11
Type of Low Voltage Distribution System	TT TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Rated Voltage (U_r)	400 V AC
Nominal AC Voltage of the System (U_o)	400 / 690 V
Voltage Rating DC	560 V

Voltage Protection Level (Up)	1.4 kV (L-N) 1.8 kV (N-PE) 2 kV
Maximum Continuous Operating Voltage (U _c)	(L-PE) 440 V
Temporary Overvoltage Test Value (U _T)	(L-N) 581 V (N-PE) 1200 V
Rated Service Short- Circuit Breaking Capacity (I _{cs})	100 kA
Discharge Current	Nominal (8 / 20 μs) 20 kA I (max, 8 / 20 μs) 80 kA
Impulse Current	I (imp, 10 / 350 μs) 6.25 kA
Short Circuit Withstand I _{cc}	100 kA
Arrester Class	II
Number of Protected Poles	4
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Poles	4
Number of Conductors	4
Position of Neutral Terminals	Right
Transmission Standard Version	Optic Plug-in
Mounting Type	DIN-Rail
Product Type	QS
Options Provided	Industry, commercial building
Auxiliary Circuit Load	Minimum 12Vdc - 10mA Maximum 250Vac - 1A
Preventive Maintenance Feature	Yes
Status Indicator	Yes
Fuse Size	4 modular spacing

Material Compliance

RoHS Information	9AKK108466A4617
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20220317
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

Dimensions

Width in Number of Modular Spacings	4
--	---

Product Net Width	71.2 mm
Product Net Height	95.8 mm
Product Net Depth / Length	76.7 mm
Product Net Weight	0.6 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	630 g

Certificates and Declarations

CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK108466A4617

Installation

Instructions and Manuals	2CTC432106M1701
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	2CTC432319D0201
Mechanical Drawings	2CTC800015F1200.pdf 2CTC800015F1201.dxf 2CTC800015F1202.stp 2CTC800015F1203.igs

Classifications

ETIM 8	EC000941 - Surge protection device for power supply systems
ETIM 9	EC000941 - Surge protection device for power supply systems
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363090
eClass	V11.0 : 27130805
Object Classification Code	141DEC

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPD Class II

