

Product No: BXTML4BEHF5

DEHN BLITZDUCTOR XT COMBINED LIGHTNING CURRENT AND SURGE ARRESTER MOD BXTML4BEHF5

FEATURES

- Space-saving combined lightning current and surge arrester module
- With LifeCheck feature for protecting four single lines sharing a common reference potential as well as high-frequency transmissions without galvanic isolation
- LifeCheck detects thermal or electrical overload, indicates arrester has to be replaced
- This status is indicated contactlessly by the DEHNrecord LC / SCM / MCM reader



General Information	
Brand	DEHN
Product Type	Surge Protection Device
Reference No.	920370
Suitable For	Pluggable DIN Rail Mounted

Technical Attributes	
Earth Fault Protection	DIN rail (top hat rail)
Lightning Impulse Current (10/350 µs) - Iimp (kA)	10
Maximum Continuous Voltage AC (V)	4.2
Maximum Continuous Voltage DC (V)	6
Nominal Discharge Current (8/20µs) - In (kA)	20
Nominal Load Current AC - I⊠ (A)	1
Nominal Voltage DC (V)	5
Voltage Protection Level - Up (kV)	11

Dimensions	
Dimensions (mm)	12W x 45H x 51D
Weight (g)	24



Protection & Standards	
Degree of Protection	IP20
Resources	
Product catalogue (Flipbook)	Download from here