

## Product No: SH203C6

### ABB SH203C6 MCB 6kA 3P 6A 400VAC C CURVE DOMESTIC

#### FEATURES

- Protection against short circuit and thermal overload
- 3P: 6kA @ 400VAC to AS/NZS60898.1
- For load centre applications only, cannot be chassis mounted



#### General Information

Brand	ABB
Product Type	MCB
Series	SH200

#### Technical Attributes

Application	Domestic
Curve Type	C Curve
Maximum Operational Voltage AC (V)	440
Minimum Operational Voltage AC (V)	12
No. of Poles	3P
Power Loss (W)	2/Pole
Rated Conditional Short-Circuit Current - Inc (kA)	6
Rated Current (A)	6
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	440
Rated Operational Voltage AC (V)	400
Rated Short-Circuit Capacity - Icn (kA)	6
Rated Voltage AC (V)	400

#### Physical Attributes

Housing Material	Insulation Group II, RAL 7035
------------------	-------------------------------

Mounting Type DIN Rail

---

### Dimensions

Cable Cross Section - Flexible (mm <sup>2</sup> )	Top/Bottom - 16/16
Cable Cross Section - Solid/Stranded (mm <sup>2</sup> )	Top/Bottom - 25/25
Dimensions (mm)	85H x 69D x 52.5W
Pole Width (mm)	17.5

---

### Protection & Standards

Degree of Protection	IP20
Pollution Degree	2
Standards and Approvals	AS/NZS 60898-1

---

### Resources

Product catalogue (Flipbook) [Download from here](#)

---