

Motor data sheet

M3BP 280SMD 4

Definition	Data	Unit	Remarks
Product code	3GBP282240-***K		CalcId: 3GZF021028-1378
Voltage code	D		
Type/Frame	M3BP 280SMD 4		
Design	High-output		
Efficiency class	IE3		IEC 60034-2-1:2014
Rated output P_N	110	kW	
Rated voltage U_N	415	V	± 5 % (IEC 60034-1)
Rated frequency f_N	50	Hz	± 2 % (IEC 60034-1)
Rated speed n_N	1487	r/min	
Rated current I_N	191	A	
Starting current I_S/I_N	7.7		
Nominal torque T_N	707	Nm	
Locked rotor torque T_l/T_N	2.9		
Maximum torque T_b/T_N	3.2		
Efficiency - full load 100%	95.4	%	IEC 60034-2-1:2014
Efficiency - 75%	95.6	%	
Efficiency - 50%	95.2	%	
Power factor - full load 100%	0.83		
Bearing DE/NDE	6316/C3 6316/C3		
Sound pressure level L_{pA} dB	76	dB(A)	+3dB(A)
Moment of inertia $J = \frac{1}{4} GD^2$ kgm ²	2	kg-m ²	
Weight	750	kg	
Ambient temperature	40	°C	
Motor losses at VSD operating points	losses in efficiency %	losses in Watt	losses in relative to nom. power %
VSD Speed 90% Torque 100%	94.9	5320	4.8
VSD Speed 50% Torque 100%	92.9	4203	3.8
VSD Speed 25% Torque 100%	87.8	3821	3.5
VSD Speed 90% Torque 50%	94.2	3048	2.8
VSD Speed 50% Torque 50%	93.1	2038	1.9
VSD Speed 50% Torque 25%	90.3	1477	1.3
VSD Speed 25% Torque 25%	86.1	1110	1.0