

Product No: 267055

STAHL 6402/4148-6100-152-2220-22-8500 LINEAR LUMINAIRE WITH LED GRP 267055

FEATURES



- Linear LED luminaire suitable for hazardous areas
- Voltage range: 100-240 VAC or 110-250 VDC
- Power consumption: 42 W
- Luminous efficacy: 138 lm/W
- Light output: 5810 lumens
- Light color: Neutral white
- Beam angle: 120 ° x 120 ° with diffusing glass
- Operating temperature range: -40 °C to +55 °C (T100 °C)
- Through wiring capability up to max. 3x16 A

General Information

Brand	STAHL
Product Type	Linear
Series	6402/4

Technical Attributes

Conductor Cross Section (mm ²)	2.5
Lamp Wattage (W)	42
Maximum Operational Voltage AC (V)	240
Maximum Operational Voltage DC (V)	250
Minimum Operational Voltage AC (V)	110
Minimum Operational Voltage DC (V)	110
No. of Conductors	5
Nominal Power (W)	42
Rated Maximum Operational Voltage AC (V)	240
Rated Maximum Operational Voltage DC (V)	250
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110

Physical Attributes

Ambient Temperature Range (°C)	-40 to +55
Maximum Temperature (°C)	55
Minimum Temperature (°C)	-40
Mounting Type	Surface
No. of Holes	3 x M20

Dimensions

Terminal Size (mm ²)	6
----------------------------------	---

Protection & Standards

Degree of Protection	IP66/67
Standards and Approvals	ATEX/IECEx

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------