

Product No: ISDA068055R1

ABB XT3N 250 TMD 100-1000 3P F F ISDA068055R1

FEATURES

- Fixed Three Pole
- Front Terminals
- Thermo-magnetic release
- ABB EcoSolutions



General Information

Brand	ABB
Product Type	MCCB
Version	Fixed

Technical Attributes

Design of Control Element	Toggle
Breaking Capacity 415V AC - I _{cu} (kA)	36
I - Short-circuit Current Setting I ₃ (A)	1000
L - Overload Current Setting I _l (A)	70 - 100
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Front Side
No. of Poles	3
Overload Release Current Setting (A)	70
Power Loss (W)	5.6
Rated Current (A)	100
Rated Frequency (Hz)	50/60
Rated Instantaneous Short-Circuit Current - I _i (A)	1000
Rated Insulation Voltage (V)	800
Rated Uninterrupted Current - I _u (A)	250
Rated Voltage (V)	690
Trip Unit	TMD

Dimensions

Dimensions (mm)	105W x 150H x 70D
-----------------	-------------------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	IEC 60947-2
-------------------------	-------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------