

Product No: OT16F3

ABB OT16F3 SWITCH-DISCONNECTOR OT16F3

FEATURES

- Front operated, 3 pole switch disconnecter
- Base mounted, DIN-rail mountable
- Non-fusible disconnect switch with front protected clamp terminals
- Switches operating mechanism on top of the switch
- Degree of protection: Front IP20



General Information	
Brand	ABB
Product Type	Manual
Suitable For	Distribution Board Installation
Type	Main Switch

Technical Attributes	
Conventional Free-Air Thermal Current - Ith (A)	25
Conventional Thermal Current - Ithe (A)	25
Main Circuit Electrical Connection	Screw Connection
Maximum Operational Voltage AC (V)	750
Mode of Operation	Front Operated
No. of Poles	3
Operating Mechanism	Mechanism on Top of the Switch
Power Loss (W)	0.3/Pole
Product Quantity	10
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	750
Rated Operational Current AC-21A 415V (A)	16
Rated Operational Current AC-22A 380-415V (A)	16
Rated Operational Current AC-22A 500V (A)	16
Rated Operational Current AC-22A 690V (A)	16

Rated Operational Current AC-23A 380-415V (A)	16
Rated Operational Current AC-23A 500V (A)	16
Rated Operational Current AC-23A 690V (A)	16
Rated Operational Power AC-23A 380-415V (kW)	7.5
Rated Operational Power AC-23A 400-415 V (kW)	7.5
Rated Operational Power AC-23A 500V (kW)	7.5
Rated Operational Power AC-23A 690V (kW)	7.5
Rated Operational Voltage (V)	750
Rated Short-Time Withstand Current - I _{cw} (kA)	0.5
Rated Short-time Withstand Current - I _{cw} (kA/1s)	0.5
Rated Uninterrupted Current - I _u (A)	25
Terminal Type	Screw Terminals

Physical Attributes

Mounting Type	Base Mount
---------------	------------

Dimensions

Cable Cross Section (mm ²)	0.75 - 10
Dimensions (mm)	35W x 68H x 56D

Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3
Standards and Approvals	IEC 60947-3 / UL 508 / CSA C22.2 No. 14

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------