

Product No: YR2.DIODE

PULS DIODE REDUNDANCY MODULE 12-48VDC 20A YR2.DIODE

FEATURES

- Cost effective solution to build redundant systems
- Dual input with single output
- Two diodes (common cathode)
- DC 12-48V +-25% Wide-range input
- Full power between -40°C and +60°C
- Width only 32mm
- Rugged metal housing
- Quick-connect spring-clamp terminals
- Easy wiring: Distribution terminal for negative pole included



General Information

Brand	PULS
Country of Origin	China / Czech Republic
Customs Tariff Number	85044083
E Classification	E-CS03
Product Type	Diode
Range	DIMENSION
Series	Y series
Warranty Period (Months)	36

Technical Attributes

Connection Type	Spring clamps
Derating	12 W/°C
Derating Temperature (°C)	+60 to +70
Efficiency	%
Input Voltage Range DC (V)	12, 24, 48
Maximum Input Voltage DC (V)	48
Maximum Output Short-circuit Current (A)	25
Minimum Input Voltage DC (V)	12
Minimum Output Current (A)	20

Nominal Current Per Input (A)	10
Output Voltage (V)	12-48
Power Loss (W)	17
Power Loss No Load (W)	0
Rated Current (A)	20
Special Application	Hazardous location, Marine
Use In Crosslinking	Yes
Voltage Drop (mV)	800

Physical Attributes

Conformal Coating	No
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-40 to 70

Dimensions

Dimensions (mm)	32W x 124H x 102D
Weight (g)	290

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	ATEX EN 60079, Class I Div. 2 Canada - CSA, Class I Div. 2 USA - CSA, EU Declaration of Conformity, IECEx IEC 60079, IEC 60950 CB Scheme, Marine ABS, Marine DNV, UL 508 Canada, UL 508 USA, UL 60950-1 Canada, UL 60950-1 USA, UK Declaration of Conformity

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------