

## Product No: MCB-20B

### ABB CONTACT BLOCK 2NO REAR MOUNT MCB-20B



#### General Information

Accessory Type	Contact Block
Brand	ABB
Product Type	Accessory
Suitable For	Pilot Devices

#### Technical Attributes

Connecting Capacity	Flexible with Ferrule 1/2 x 0.75 - 2.5mm <sup>2</sup> Flexible with Insulated Ferrule 1/2 x 0.75 - 2.5mm <sup>2</sup> Flexible 1/2 x 0.75 - 2.5mm <sup>2</sup> Solid 1/2 x 0.75 - 2.5mm <sup>2</sup>
Connection Type	Screw Clamp
Function	Without holder
Illumination	Non-illuminated
No. of Normally-open Contacts	2
Power Loss (W)	5
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-15 230V (A)	6
Rated Operational Current DC-13 125V (A)	0.55
Rated Operational Current DC-13 24V (A)	5
Rated Operational Voltage (V)	690 (Maximum)
Rated Operational Voltage AC/DC (V)	690

Terminal Type	Screw
Tightening Torque (Nm)	0.9
Wire Stripping Length (mm)	8

#### Physical Attributes

Ambient Temperature Range (°C)	-25 to 70
Mounting Type	Rear Mount
Storage Temperature Range (°C)	-40 to 85

#### Dimensions

Dimensions (mm)	20W x 44H x 28D
Weight (kg)	0.04

#### Protection & Standards

Degree of Protection	Terminals: IP20
Pollution Degree	3

#### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------