

## **Product No: 942 103-001**

## HIRSCHMANN INDUSTRIAL FIREWALL AND SECURITY ROUTER WITH EXTENSIVE LAYER 2 AND LAYER 3 REDUNDANCY FAST ETHERNET ATURES, 2X FAST ETHERNET TX 942103001

## **FEATURES**

- Industrial firewall and security router with extensive Layer 2 and Layer 3 redundancy features
- DIN rail mounted
- Fanless design



General Information	
Brand	HIRSCHMANN
Product Type	Industrial Router
Series	EAGLEONE

Technical Attributes	
Configuration	Hirschmann Standard Configuration
No. of 100Mb Ports	2
No. of Ethernet Ports	2
No. of Ports	2xFast Ethernet Ports (10/100 Mbit/s), 2xTwisted Pair RJ45
Nominal Power (W)	5
Rated Maximum Operational Voltage AC (V)	30
Rated Maximum Operational Voltage DC (V)	60
Rated Minimum Operational Voltage AC (V)	18
Rated Minimum Operational Voltage DC (V)	9.6
Rated Operational Voltage AC (V)	18-30
Rated Operational Voltage DC (V)	9.6-60

Physical Attributes	
Maximum Temperature (°C)	70
Minimum Temperature (°C)	-40
Mounting Type	DIN Rail



Operational Temperature Range (°C) +0 to +60

Protection & Standards	
Degree of Protection	IP20
Standards and Approvals	CE, FCC, EN 61131, EN 60950, CUL508

Resources	
Product catalogue (Flipbook)	Download from here