

Product No: VB6A400080

ABB VB6A-40-00-80 MINI REVERSING CONTACTOR 220 ... 240 V AC - 4 NO - 0 NC - SCREW TERMINALS VB6A400080

FEATURES

- Very compact, falt design
- Easy and quick mounting in any position
- Compact reversing contactor as one module, including blocking function
- Low power consumption
- Positive linked and guided contacts
- Hum-free operating DC coil



General Information

Brand	ABB
Product Type	Mini Contactor

Technical Attributes

Actuating Voltage Type	AC
Contacts	4NO (Main Contacts)
Function	Reversing Contactor
Main Circuit Electrical Connection	Screw Connection
No. of Normally-open Contacts	4
No. of Poles	4
Operating Voltage AC (V)	690
Operating Voltage Type	AC
Power Loss (W)	1.0/pole AC-1
Rated Control Circuit Voltage AC (V)	220 - 240
Rated Control Supply Voltage AC (V)	220
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-1 240V (A)	20
Rated Operational Current AC-1 690V (A)	6
Rated Operational Power AC-3 400V (kW)	4
Rated Operational Voltage AC (V)	690

Technical Attributes

Rated Operational Voltage DC (V)	220
Rated Supply Voltage AC (V)	220
Terminal Type	Screw

Physical Attributes

Mounting Type	Rail Mount
Operational Temperature Range (°C)	-20 to +55

Dimensions

Dimensions (mm)	96.2W x 57.5H x 46.7D
-----------------	-----------------------

Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3