

Product No: 250250115100H001B2000

BD SENSORS DMK331 INDUSTRIAL PRESSURE TRANSMITTER DMK331 INDUSTRIAL PRESSURE TRA 250250115100H001B2000

FEATURES

- Pressure port G 1/2" flush for pasty
- and polluted media.
- Pressure port G 1/2" open port PVDF for aggressive media.

General Information	
Brand	BD SENSORS
Product Series	DMK 331
Product Type	Ceramic Sensor
Version	Standard

Accuracy	0.5 % FSO
Application	Plant and machine engineering. Energy industry. Environmental engineering (water - sewage - recycling). Medical technology (Specially for oxygen application).
Electrical Connection	Male and female plug ISO 4400
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Input Pressure (bar)	2.5
Mechanical Connection	G1/2" DIN 3852 open pressure port
Mechanical Stability	Vibration: 10 g RMS (25 2000 Hz) according to DIN EN 60068-2-6. Shock: 500 g / 1 msec according to DIN EN 60068 2-27.
Operational Life	100 million load cycles
Output Signal	4 20 mA / 2-wire

Physical Attributes



Permissible Temperatures	Medium: -40 125 °C Electronics / Environment: -40 85 °C Storage: -40 100 °C
Pressure Port	PVDF (PVDF only with G1/2" DIN 3852 open pressure port (up to 60 bar); permissible medium temperature: -30 60 °C)
Response Time (ms)	≤10
Seals	FKM

Diaphragm Material	Ceramics Al2O3 96 %	
Resources		
Product catalogue (Flipbook)	Download from here	