


Product No: MC2A400ATN

ABB MC2A400ATN MINI CONTACTOR 50 HZ 220 ... 240 V AC - 4 NO - 0 NC - SCREW TERMINALS MC2A400ATN

FEATURES

- Compact design, ideal for installations with limited space
- Enables control of both single and three-phase loads
- Secure and convenient electrical connections
- Options for wall or rail mounting to accommodate different installations needs



General Information

Brand	ABB
Product Type	Mini Contactor
Series	M

Technical Attributes

Actuating Voltage Type	AC
Main Circuit Electrical Connection	Screw Connection
Mode of Operation	AC
No. of Normally-open Contacts	4
No. of Poles	4
Operating Voltage AC (V)	440
Power Loss (W)	0.7/pole AC-1
Rated Control Circuit Voltage AC (V)	220 - 240
Rated Control Supply Voltage AC (V)	220
Rated Control Supply Voltage DC (V)	220
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	750
Rated Operational Current AC-1 400V (A)	20
Rated Operational Power AC-3 400V (kW)	5.5
Rated Operational Voltage AC (V)	440
Rated Supply Voltage AC (V)	220

Technical Attributes

Terminal Type	Screw
---------------	-------

Physical Attributes

Mounting Type	DIN Rail / Wall
---------------	-----------------

Operational Temperature Range (°C)	-40 to +55
------------------------------------	------------

Dimensions

Dimensions (mm)	45W x 48H x 56D
-----------------	-----------------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------