

Product No: MCB-10G

ABB CONTACT BLOCK INO FRONT MOUNT MCB-10G



General Information

Accessory Type	Contact Block
Brand	ABB
Product Type	Accessory
Suitable For	Pilot Devices

Technical Attributes

Connecting Capacity	Flexible with Ferrule 1/2 x 0.75 - 2.5mm ² Flexible with Insulated Ferrule 1/2 x 0.75 - 2.5mm ² Flexible 1/2 x 0.75 - 2.5mm ² Solid 1/2 x 0.75 - 2.5mm ²
Connection Type	Screw Clamp
Illumination	Non-illuminated
No. of Normally-open Contacts	1
Power Loss (W)	2.5
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	690
Rated Operational Current AC-15 230V (A)	6
Rated Operational Current DC-13 125V (A)	0.55
Rated Operational Current DC-13 24V (A)	5
Rated Operational Voltage AC/DC (V)	690
Terminal Type	Screw
Tightening Torque (Nm)	0.9

Wire Stripping Length (mm)	8
----------------------------	---

Physical Attributes

Ambient Temperature Range (°C)	-25 to 70
--------------------------------	-----------

Mounting Type	Front Mount
---------------	-------------

Storage Temperature Range (°C)	-40 to 85
--------------------------------	-----------

Dimensions

Dimensions (mm)	10W x 44H x 28D
-----------------	-----------------

Weight (kg)	0.04
-------------	------

Protection & Standards

Degree of Protection	Terminals: IP20
----------------------	-----------------

Pollution Degree	3
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
