

Product No: 257209

STAHL METAL POSITION SWITCH SERIES 8074/2 257209

FEATURES

- - High-quality metal Ex e enclosure
- - Slow-action contact functions
- - Degree of protection IP66/67

General Information

Brand	STAHL
Product Type	Switch

Technical Attributes

Application	Application range (zones) - 1, 2, 21, 22
Clamping Range (mm)	4 - 13
Contact Material	Silver-Nickel
Contacts	2NC
Fuse Type	gL/gG
Rated Operational Current (A)	4.4 - 6.6
Rated Operational Voltage AC (V)	Equal potential- 400, Unequal potential - 250
Rated Operational Voltage DC (V)	125
Surge Voltage (kV)	4
Tightening Torque (Nm)	Screw Terminals: 0.4 Nm Maximum; Cover Screws: 1.5 - 2 Nm

Physical Attributes

Ambient Temperature Range (°C)	-40 to +70
Colour	Enclosure - Black/Silver
Enclosure Material	Corrosion-resistant aluminium, powder-coated
Material	Cover - 1.4401 blasted stainless steel, Cable gland - Polyamide, Glass fibre reinforced

Dimensions



Cable Cross Section (mm ²)	0.75 - 2.5, Earth - Maximum - 4
--	---------------------------------

Protection & Standards

Certifications	European Union (ATEX), IECEx
----------------	------------------------------

Degree of Protection	IP66
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
