

Product No: 101152789

SCHMERSAL ENCLOSED SAFETY SOLENOID INTERLOCK 101152789

Note: Individual coding available on request



General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	Low
EAN	4030660000000
eCl@ss Number, Version 11.0	27-37-12-43
eCl@ss Number, Version 9.0	23-13-01-03
ETIM 6.0	EC001029
ETIM 7.0	EC002593
Housing Construction Form	Norm construction design
Product Type	Solenoid
Working Principle	Electromechanical

Technical Attributes

No. of Auxiliary Contacts	1
Contact Material	Silver
Maximum Actuating Speed (m/s)	1
Maximum Cable Cross Section (mm ²)	2 x 2.5
Maximum Fuse Rating	10 A gG D-fuse slow blow
Minimum Actuating Speed (mm/min)	24
Minimum Cable Cross Section (mm ²)	0.75
Minimum Mechanical Life	1000000 Operations
Minimum Positive Break Force (N)	20

No. of Safety Contacts	1
Overvoltage Category	3
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	500
Rated Short-circuit Current (A)	1000
Resistance to Shock (g/ms)	30 / 11
Switching Element	NC contact, NO contact
Switching Principle	Slow action
Terminal Type	Screw terminals M20 x 1.5
Utilisation Category	DC-13 AC-15
Utilisation Category DC-13	0.25 A

Physical Attributes

Actuator Type	Magnet
Enclosure Material	Aluminium
Gross Weight (g)	35
Maximum Ambient Temperature (°C)	70
Minimum Ambient Temperature (°C)	-15
Net Weight (g)	55
Storage Temperature (°C)	-25 to 85
Wire Cross-Section	0.34 mm

Dimensions

Sensor Height (mm)	171.5
Sensor Length (mm)	38

Protection & Standards

Degree of Protection	IP65
Standards	EN IEC 61496-1 / CLC/TS 61496-2

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------