

ABB BW325TPN POLYCARBONATE ENCLOSED SWITCH DISCONNECTOR 32A 3P SIDE OPERATED

BW325TPN

FEATURES

- 3 pole, Enclosed switch disconnecter
- Plastic Enclosure
- Grey side-operated handle
- Interlocked cover
- Enclosure is UV protected, protected against low-pressure water jets
- Membrane grommets are included (IP54)
- Handle is padlockable and made for 1 padlock
- The switch is made for 5 wire system and have a fixed neutral terminal and PE terminal
- Degree of protection: IP65



GENERAL INFORMATION

Brand	ABB
Product Type	Enclosed

TECHNICAL ATTRIBUTES

Conventional Free-Air Thermal Current - I _{th} (A)	32
Conventional Thermal Current - I _{the} (A)	25
No. of Poles	3P
Rated Current (A)	25
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	690
Rated Operational Current AC-22A 380-415V (A)	25
Rated Operational Current AC-22A 690V (A)	16
Rated Operational Current AC-23A 380-415V (A)	16
Rated Operational Current AC-23A 500V (A)	16
Rated Operational Current AC-23A 690V (A)	10
Rated Operational Power AC-23A 380-415V (kW)	7.5
Rated Operational Power AC-23A 500V (kW)	7.5
Rated Operational Power AC-23A 690V (kW)	7.5
Rated Operational Voltage (V)	690

PHYSICAL ATTRIBUTES

Colour	Light Grey
--------	------------

PHYSICAL ATTRIBUTES

Enclosure Material	Plastic
Handle Colour	Dark Grey
Handle Type	Side-Operated
Included	Handle

DIMENSIONS

Cable Cross Section (mm ²)	0.75-10
Dimensions (mm)	111W X 130H X 60D

PROTECTION & STANDARDS

Degree of Protection	IP65
Impact Resistance Rating	Housing IK08
Standards and Approvals	IEC 60947-1, IEC 60947-3

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------