

Product No: DS201MC10A30

ABB DS201MC10A30 RCBO 10kA IP+N 10A C CURVE TYPE A 30mA

FEATURES

- - Protection against short circuit, thermal overload and earth leakage
- - Contact Position Indication (CPI)
- - Earth fault indicator to identify easier earth faults
- - Test pushbutton to verify the correct functioning of the device
- - Laser printed data for quick identification
- - Finger safety with IP20 terminals
- - Pole configuration IP+N



General Information

Brand	ABB
Product Type	RCBO
Series	DS201M

Technical Attributes

Application	Commercial and Industrial
Breaking Capacity 230V AC - I _{cu} (kA)	15
Curve Type	C Curve
No. of Poles	IP+N
Power Loss (W)	1.8
Rated Conditional Short-Circuit Current - I _{nc} (kA)	15
Rated Current (A)	10
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230/240
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - I _{cn} (kA)	10
Rated Voltage AC (V)	230

Test Voltage (kV)	0.17-0.264
-------------------	------------

Type of Residual Current	A
--------------------------	---

Physical Attributes

Housing Material	Insulation Group I - II, RAL 7035
------------------	-----------------------------------

Mounting Type	DIN Rail
---------------	----------

Protection & Standards

Degree of Protection	IP40 (Housing), IP20 (Terminals)
----------------------	----------------------------------

Pollution Degree	2
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------