

## Product No: BCOMODML2BD48

### DEHN PROTECTION MODULE FOR 1 PAIR BLITZDUCTORCONNECT W. FAULT INDICATION BCOMODML2BD48

#### FEATURES

- Pluggable combined arrester module
- Tested to EN/IEC 61643-21
- Energy coordinated according to IEC 61643-22
- Width of 6 mm
- Replacement module



#### General Information

Article No.	927045
Brand	DEHN
Product Type	Signal Line Protector

#### Technical Attributes

Lightning Impulse Current (10/350 $\mu$ s) - Iimp (kA)	1.5 (Per Line)
Maximum Continuous Operating Voltage MCOV AC (V)	38.1
Maximum Continuous Operating Voltage MCOV DC (V)	56
Maximum Discharge Current (8/20 $\mu$ s) - I <sub>max</sub> (kA)	20
Nominal Discharge Current (8/20 $\mu$ s) - I <sub>n</sub> (kA)	5 (Per Line)
Nominal Voltage (V)	48
Operating State/Fault Indication	Green/Red
Total Discharge Current (10/350 $\mu$ s) - I <sub>total</sub> (kA)	3
Total Discharge Current (8/20 $\mu$ s) - I <sub>total</sub> (kA)	10
Voltage Protection Level - U <sub>p</sub> (kV)	$\leq 0.09$ (Line-Line)/ $\leq 0.6$ (Line-PG)

#### Physical Attributes

Pluggable	Plugs in to BCO Base Part
-----------	---------------------------

#### Dimensions

Dimensions (mm)	0.08W x 0.12L x 0.01D
-----------------	-----------------------

Module Width (mm)	6
-------------------	---

Weight (kg)	0.04
-------------	------

### Protection & Standards

Degree of Protection	IP20
----------------------	------

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------