

Product No: CBLUSBMI

RED LION USB TETHERING CABLE, 1M METAL JACKETED CBLUSBMI

FEATURES

- PID Controller with multiple DIN sizes: 1/4, 1/8, and 1/16
- Power Connection options: AC 100 to 240 VAC or DC 24 VDC
- Excitation current for RTD: 180 mA
- Process Inputs: Voltage (0-5V or 0-10V) and Current (0-20mA or 4-20mA), plus a low voltage range of 0-50 mV
- Optional CT Input for AC current measurement: 0 to 25 mA AC, Single phase
- Remote Input compatibility: Voltage (0-10V) and Current (0-20mA or 4-20mA)
- Main Control Output range: 0 to 10 VDC
- Communication via RS-485 serial interface



General Information

Brand	RED LION
Product Type	Accessory
Series	PXU
Type	Armoured

Technical Attributes

Nominal Power (W)	5
Rated Maximum Operational Voltage AC (V)	240
Rated Minimum Operational Voltage AC (V)	100

Physical Attributes

Maximum Temperature (°C)	50
Minimum Temperature (°C)	0

Dimensions

Cable Length (m)	1
------------------	---

Protection & Standards

Degree of Protection

IP65

Resources

Product catalogue (Flipbook)

[Download from here](#)