

## Product No: 101128110

### SCHMERSAL M2S 6610-10-KZ-2028 6.0MMICRO SWITCH 101128110



#### General Information

Brand	SCHMERSAL
-------	-----------

#### Technical Attributes

Contact Material	Gold-plated Silver (AgNi 15 + Au 0.3µm)
Maximum Fuse Rating	4 A gG D-fuse
Minimum Actuating Speed (mm/min)	10
Minimum Mechanical Life	3000000 Operations
No. of Normally-open Contacts	1
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	250
Rated Operational Current AC-15 (A)	1
Rated Operational Voltage AC-15 (V)	230V AC
Switching Frequency	30000/h
Switching Principle	Snap Action with Self-cleaning Contact
Thermal Test Current (A)	4
Utilisation Category	AC-15

#### Physical Attributes

Housing Material	Glass-fibre, Reinforced Thermoplastic
Maximum Ambient Temperature (°C)	80
Minimum Ambient Temperature (°C)	-30

## Dimensions

Wire Cross Section (mm <sup>2</sup> )	0.75mm <sup>2</sup> (Diameter)
---------------------------------------	--------------------------------

## Protection & Standards

Degree of Protection	IP67
----------------------	------

Standards and Approvals	EN IEC 60947-5-1
-------------------------	------------------

## Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------