

Product No: BXTML4BE24

DEHN BXTML4BE24 BLITZDUCTOR XT COMBINED ARRESTER T1, In=20KA

FEATURES

- - Space-saving
- - For protecting four single lines
- - LifeCheck SPD monitoring
- - Standards IEC/EN 61643-21



General Information

| | |
|--------------|-----------------------|
| Article No. | 920324 |
| Brand | DEHN |
| Product Type | Signal Line Protector |

Technical Attributes

| | |
|--|--|
| Lightning Impulse Current (10/350 μ s) - Iimp (kA) | 2.5 (Per Line) |
| Maximum Continuous Operating Voltage MCOV AC (V) | 23.3 |
| Maximum Continuous Operating Voltage MCOV DC (V) | 33 |
| Nominal Discharge Current (8/20 μ s) - In (kA) | 10 (Per Line) |
| Nominal Voltage (V) | 24 |
| Total Discharge Current (10/350 μ s) - Itotal (kA) | 10 |
| Total Discharge Current (8/20 μ s) - Itotal (kA) | 20 |
| Voltage Protection Level - Up (kV) | ≤ 0.102 (Line-Line)/ ≤ 0.066 (Line-PG) |

Physical Attributes

| | |
|-----------|----------------------|
| Pluggable | Plugs into Base Part |
|-----------|----------------------|

Dimensions

| | |
|-------------------|----|
| Module Width (mm) | 12 |
|-------------------|----|

Protection & Standards

| | |
|----------------------|------|
| Degree of Protection | IP20 |
|----------------------|------|

Resources

Product catalogue (Flipbook)

[Download from here](#)
