

Product No: HS6B-12B03

IDEC HS6E SUBMINIATURE INTER LOCK SWITCH, 1NO, 2NC WITH 3m CABLE HS6B-12B03

FEATURES

- Integral molded cable reduces wiring time
- watertight sealing (contact is sealed; housing allows drainage)
- Direct Opening Action: Opening the door forces the contacts to disconnect even if the contacts are welded
- (IEC/ENC60947-5-1)
- Keys comply with ISO14119 and EN1088
- B10d: 2.0E+06



General Information

Brand	IDEC
Product Type	Safety Interlock Switch

Technical Attributes

Minimum Electrical Life	100000
Minimum Mechanical Life	1000000
No. of Normally-closed Contacts	2
No. of Normally-open Contacts	1
Rated Insulation Voltage (V)	300
Rated Thermal Current - Ith (A)	2.5

Physical Attributes

Housing Colour	Black
Operational Temperature Range (°C)	-25 to 70

Dimensions

Cable Length (m)	3
Dimensions (mm)	30W x 15H x 78D
Weight (g)	270

Protection & Standards

Degree of Protection	IP67
----------------------	------

Pollution Degree	3
------------------	---

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------