


Product No: 942 164-001

HIRSCHMANN SFP FIBER OPTIC 2.5 GIGABIT ETHERNET TRANSCEIVER SM, EXTENDED TEMPERATURE RANGE 942164001

FEATURES

- SFP Fiberoptic 2.5 Gigabit Ethernet Transceiver SM with LC connector
- Extended temperature range
- IP20 Protection Class
- 24 months of guarantee period



General Information

Brand	HIRSCHMANN
Product Type	Transceiver
Series	M-SFP
Software Diagnostics	Optical input and output power, transceiver temperature

Technical Attributes

Electromagnetic Capability	10 V/m (80-1000 MHz)
Electrostatic Discharge (kV)	6 kV Contact Discharge, 8 kV Air Discharge
Fiber Type	Single mode fiber (9/125 μ m)
Mean Time Between Failure (MTBF)	589 Years
No. of Fiber Ports	1
No. of Ports	1 x 2.5 Gig with LC connector
Power Consumption (W)	1
Resistance to Vibrations	1 mm, 2 Hz-13.2 Hz, 90 min. 0.7 g, 13.2 Hz-100 Hz, 90 min. 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min. 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
Surge Voltage (kV)	Power Line: 2 kV (Line/Earth), 1 kV (Line/Line), 1 kV Data Line
Transition Type	2 kV power line, 1 kV data line

Physical Attributes

Fiber Cable Length (km)	0 - 20
Maximum Temperature (°C)	85
Minimum Temperature (°C)	-40
Mounting Type	SFP+ Slot
Operational Temperature Range (°C)	-40 - 85
Relative Humidity	5-95 %
Storage Temperature Range (°C)	-40 - 85

Dimensions

Dimensions (mm)	13.4W x 8.5H x 56.5D
Weight (g)	30
Weight (kg)	0.04

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------