

Product No: RLY70100

RED LION SOLID STATE RELAY 3P 4-32VDC 25A RLY70100

FEATURES

- Solid State Relay, 25Amp, Single Phase
- DIN Rail Mountable
- 12-Port Gigabit Managed Industrial Ethernet Switch
- Singlemode fiber with SC Style Connector
- PTP (Precision Time Protocol) Enabled
- Fiber Length support up to 80km
- Power Input range: 10-49 VDC
- Maximum Input Current: 780 mA @ 24 VDC



General Information

Brand	RED LION
Product Type	Accessory
Series	NT24K

Technical Attributes

Contacts	3 NO
Indication	LED "ON"
Input Current (mA)	22 - 28
Insulation Resistance (MΩ)	1000
No. of Phases	3
Output Voltage AC (V)	48 - 600
Rated Control Circuit Voltage DC (V)	4 - 32
Rated Current (A)	25
Rated Maximum Operational Voltage DC (V)	49
Rated Minimum Operational Voltage DC (V)	22
Timing Range	0.5 cycle turn-off, 0.5 cycle turn-on

Physical Attributes

Maximum Temperature (°C)	80
Minimum Temperature (°C)	-40

Operational Temperature Range (°C) -20 to +80

Protection & Standards

Degree of Protection IP20

Pollution Degree 3

Standards and Approvals UL 508, IEC 60950-1

Resources

Product catalogue (Flipbook) [Download from here](#)
