

## ABB OXB400E3S3QTEA TRUONE® ATS MILD STEEL ENCLOSED 3P+N 400A LEVEL 3 IP65

OXB400E3S3QTEA

### FEATURES

- RAL 2000 Orange.
- 1.6mm thickness mild steel
- Concealed and removable hinges with pins.
- Polyurethane sealing gaskets.
- Top and bottom glandplates.
- Switched Neutral.
- Operation temperature (-25 to 70°C).
- Voltage (200-480 VAC with +/- 20% tolerance).
- Tolerant of: Vibrations (acc. IEC 60068-2-6), Shocks (acc. IEC 60068-2-27).



### GENERAL INFORMATION

Brand	ABB
Product Type	Truone® Automatic - Enclosed

### TECHNICAL ATTRIBUTES

No. of Poles	3P + N
Rated Current (A)	400
Rated Operational Voltage AC (V)	200-480
Transition Type	Delayed

### PHYSICAL ATTRIBUTES

Colour	Orange, RAL2000
Material	Mild Steel

### DIMENSIONS

Dimensions (mm)	800H x 300D x 600W
-----------------	--------------------

### PROTECTION & STANDARDS

Degree of Protection	IP65
----------------------	------

### RESOURCES

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------

## DIMENSIONS

