

Product No: ISDA072566R1

ABB E4.2H 4000 EKIP TOUCH LSIG 3P WMP ISDA072566R1

FEATURES

- IP30 protection for fixed parts
- Lifting plates
- Adjustable rear terminals
- Racked-out mechanism lock, anti-insertion lock, standard shutter lock
- Lever for racking in/out
- AUX 4Q 400V Open-Closed changeover contact
- TU Reset push button
- S51 250V trip indicator



General Information

Brand	ABB
Product Type	Automatic ACB
Version	Withdrawable

Technical Attributes

Breaking Capacity 400V AC - Icu (kA)	100
Breaking Capacity 415V AC - Icu (kA)	100
Design of Control Element	Push Button
Earth Fault Protection	Yes
G (0.1 to 1 x In) - I4 (A)	400 - 4000
I (1.5 to 15 x In) - I3 (A)	6000 - 60000
Indication	Switched-off Indicator
L (0.4 to 1 x In) - I1 (A)	1600 - 4000
Main Circuit Electrical Connection	Connection at Separate Chassis Part
Main Current Circuit Connection Position	Connection at Separate Chassis Part
No. of Auxiliary Change-over Contacts	4
No. of Poles	3
Overload Release Current Setting (A)	1600
Power Loss (W)	900
Rated Current (A)	4000
Rated Impulse Withstand Voltage (kV)	12
Rated Instantaneous Short-Circuit Current - Ii (A)	6000

Technical Attributes

Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I _{cw} (kA/1s)	85
Rated Uninterrupted Current - I _u (A)	4000
Rated Voltage (V)	690
S (0.6 to 10 x I _n) - I ₂ (A)	2400 - 40000
Trip Unit	EKIP Touch LSIG

Dimensions

Size of Frame	E4.2
---------------	------

Protection & Standards

Degree of Protection	IP30
Standards and Approvals	IEC

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------