

Product No: 101184381

SCHMERSAL BNS260-02ZG-ST-L SAFETY SENSOR 101184381

FEATURES

- Safety sensor with thermoplastic enclosure
- Features coding for security
- Equipped with 2 openers and 1 shutter
- Includes 2 safety contacts
- Utilizes a magnet as the actuating element
- Designed for left door hinge application
- Comes with a connector terminal of 8 mm, 6-pole
- Offers latching interlocking functionality
- Switching voltage rated at 30 VDC



General Information

Brand	SCHMERSAL
EAN	4030660000000
eCl@ss Number, Version 11.0	27-27-27-04
eCl@ss Number, Version 9.0	27-27-27-03
ETIM 6.0	EC002549
ETIM 7.0	EC001487
Product Type	Safety Sensor
Series	BNS260

Technical Attributes

Contact Material	Ag-Ni, self-cleaning, positive drive
Maximum Actuating Speed (m/s)	0.3
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	10 A gG D-fuse slow blow
Minimum Cable Cross Section (mm ²)	0.25
Minimum Mechanical Life	20000000 Operations
No. of Safety Contacts	4
Nominal Output Current (A)	0.01
Nominal Power (W)	0.2
Rated Impulse Withstand Voltage (kV)	4

Rated Insulation Voltage (V)	300
Rated Maximum Operational Voltage DC (V)	24
Rated Short-circuit Current (A)	100
Switching Element	NO contact, NC contact
Switching Principle	Slow action
Terminal Type	Cable
Utilisation Category	DC-13 AC-15

Physical Attributes

Actuator Type	Roller lever H200
Enclosure Material	Plastic, glass-fibre-reinforced
Gross Weight (g)	60
Maximum Ambient Temperature (°C)	80
Maximum Temperature (°C)	70
Minimum Ambient Temperature (°C)	0
Minimum Temperature (°C)	-25
Net Weight (g)	40

Dimensions

Sensor Height (mm)	52
Sensor Length (mm)	33

Protection & Standards

Degree of Protection	IP67
Standards	EN IEC 60947-5-1 / EN ISO 13849-1 / BG-GS-ET-15

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------