

Product No: 143522

STAHL 8290/3-M20 STOPPING PLUG 143522

FEATURES

- Contact element with integrated resistors
- Rated for 30.00 VDC continuous voltage
- Comprises 2 poles
- Operating temperature range from -60 °C to +60 °C
- Protection rating of IP20
- Part of the 8208 Series by Stahl
- Certified for use in hazardous areas (ATEX/IECeX compliant)
- Meets additional standards: ATEX (PTB), Brazil (ULB), IECEx (PTB), India (PESO), SIL (exida)



General Information	
Brand	STAHL
Product Type	Accessory
Series	8290/3

Technical Attributes	
Application	Application range (zones) - 1, 2, 21, 22
Thread Size	M20

Ambient Temperature Range (°C) -60 to +80 Colour Black Drive Hexagon Socket Material Polyamide	Physical Attributes	
Drive Hexagon Socket	Ambient Temperature Range (°C)	-60 to +80
	Colour	Black
Material Polyamide	Drive	Hexagon Socket
	Material	Polyamide
Maximum Temperature (°C) 80	Maximum Temperature (°C)	80
Minimum Temperature (°C) -60	Minimum Temperature (°C)	-60

Protection & Standards	
Certifications	IECEx, ATEX, UL
Degree of Protection	IP66

IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA CONTROL BOXES > IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA ACCESSORIES



Standards and Approvals

ATEX/IECeX

Resources		
Product catalogue (Flipbook)	Download from here	