

ABB E12N3ETG8W ACB E1.2N 3P 66KA WITHDRAWABLE 800A EKIP TOUCH LSIG

E12N3ETG8W



GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I _{cu} (kA)	66
G (0.1 to 1 x I _n) - I ₄ (A)	80-800
I (1.5 to 15 x I _n) - I ₃ (A)	1200-12000
L (0.4 to 1 x I _n) - I ₁ (A)	320-800
No. of Poles	3P
Power Loss (W)	100
Rated Current (A)	800
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I _{cw} (kA/1s)	50
Rated Uninterrupted Current - I _u (A)	800
S (0.6 to 10 x I _n) - I ₂ (A)	480-8000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG



DIMENSIONS

Frame Size	E1.2
------------	------

PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------