

Product No: DSE203NMC32A30

ABB RCBO, 10kA 3P+N 32A C-CURVE 30mA DSE203NMC32A30

FEATURES

- - Protection against short circuit, thermal overload and earth leakage
- - Functional earth white cable to give additional protection in case of loss of the neutral
- - Earth fault trip indicator window
- - Real contact position indicator on toggle
- - Flying leads for installation in chassis distribution boards
- - Pole configuration 3P+N



General Information

Brand	ABB
Product Type	RCBO
Series	DSE200

Technical Attributes

Breaking Capacity 415V AC - I _{cu} (kA)	10
Curve Type	C Curve
No. of Poles	3P+N
Rated Current (A)	32
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	415
Rated Residual Current (mA)	30
Terminal Type	Pillar terminals
Type of Residual Current	A

Physical Attributes

Operational Temperature Range (°C)	-25 to +70
------------------------------------	------------

Dimensions

Dimensions (mm)	53.4Wx117.5Hx71.6D
-----------------	--------------------

Protection & Standards

Degree of Protection	IP40 (Housing), IP20 (Terminals)
----------------------	----------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
