

CA710/2



External Comb Type Shorting Link

External shorting links bridge potentials between terminal blocks, reducing wiring time. Adjacent or selected blocks within an assembly can be easily interconnected. Individual links may be removed for selective shorting. These are insulated and available in 2, 3, 4 and 10 pole versions. They are made of tin plated brass/copper. Comb Link must be tightened to the recommended torque specified to get a reliable connection.

PRODUCT SPECIFICATION

Rated Current	41 A
Torque	0.8 Nm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA710/2	External Comb Type Shorting Link available in 2 Pole	100
CA710/3	External Comb Type Shorting Link available in 3 Pole	50
CA710/4	External Comb Type Shorting Link available in 4 Pole	50
CA710/10	External Comb Type Shorting Link available in 10 Pole	20

SUITABLE FOR

CDTTUFTSC	10 sq.mm Spring Loaded Feed Through Terminal Blocks
CTS6U	6 sq.mm Standard Feed Through Terminal Blocks
CDTTU	6 sq.mm Disconnect & Test Terminal Blocks
CDTTUFT	10 sq. mm Feed Through Terminal Blocks
CDTTUSC	10 sq.mm Disconnect & Test Terminal Blocks
CDTTUSH	Disconnect & Test Terminal Block
CKT6U	6 sq.mm Knife Type Disconnect & Test Terminal Blocks with Socket screws