

Product No: AF205301111

ABB AF205301111 AF CONTACTOR 3P, 350A (AC-1), 110KW 415VAC CONTROL 24-60VAC/20-60VDC, 1NO+1NC

FEATURES

- - 3 pole contactor with pre-mounted auxiliary contacts and double clamp
- Reduce panel energy consumptions thanks to AF technology
- - Ensure distinct operations in unstable networks
- - Built-in surge protection, offering a compact solution



| General Information | |
|---------------------|--------------|
| Brand | ABB |
| Product Type | AF Contactor |

| Technical Attributes | |
|---|---------------------|
| Auxiliary Contacts | INO/INC |
| Contacts | 3NO (Main Contacts) |
| No. of Poles | 3P |
| Rated Control Circuit Voltage AC (V) | 24 - 60 |
| Rated Control Circuit Voltage DC (V) | 20 - 60 |
| Rated Frequency (Hz) | 50/60 |
| Rated Impulse Withstand Voltage (kV) | 8 |
| Rated Insulation Voltage (V) | 1000 |
| Rated Operational Current AC-1690V (A) | 350 |
| Rated Operational Current AC-3 415V (A) | 205 |
| Rated Operational Power AC-3 400V (kW) | 110 |
| Rated Operational Voltage AC (V) | 1000 |
| Short-Circuit Protective Device | 400A, fuse type gG |
| Terminal Type | Main Circuit: Bars |

Physical Attributes



| Mounting Type | Panel |
|-----------------|--------------------|
| | |
| Dimensions | |
| Dimensions (mm) | 196H x 152D x 105W |
| | |

Protection & Standards

Degree of Protection

IP20 (Coil Terminals)

Resources

Product catalogue (Flipbook)

Download from here