

Product No: 500100113100Z00112000

BD SENSORS DMP331P INDUSTRIAL PRESSURE TRANSMITTER DMP331P INDUSTRIAL PRESSURE TR 500100113100Z00112000

FEATURES

- Hygienic version.
- Diaphragm with low surface roughness.
- CIP/SIP cleaning up to 150 °C.
- Vacuum resistant.

General Information	
Brand	BD SENSORS
Product Series	DMP 331P
Product Type	Stainless Steel Sensor
Version	Standard

Technical Attributes	
Accuracy	Standard for pN ≥ 0.4 bar: 0.35 % FSO
Application	Food and beverage related applications. Pharmaceutical industry.
Electrical Connection	Male and female plug ISO 4400
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326.
Input Pressure (bar)	1.0
Mechanical Connection	G1/2" with flush welded diaphragm (DIN 3852) [Possible only for pN≥1 bar]
Mechanical Stability	Vibration: G 1/2": 20 g RMS (25 2000 Hz), Others: 10 g RMS (25 2000 Hz) according to DIN EN 60068-2-6. Shock: G 1/2": 500 g / 1 msec, Others: 100 g / 1 msec according to DIN EN 60068-2-27.
Operational Life	100 million load cycles.
Output Signal	4 20 mA / 2-wire
Permissible Temperatures	Medium: −10 125 °C Medium with Cooling Element: −10 250 °C/−10



	150 °C (Overpressure/Vacuum) Electronics / Environment: -40 85 °C Storage: -40 100 °C
Response Time (ms)	< 10
Seals	For inch thread - standard: FKM

Physical Attributes	
Diaphragm Material	Stainless steel 1.4435 (316L)
Filling Fluid Type	Food compatible oil (FDA) / 3A

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>