

Product No: XRG3-50/5-3P

ABB XRG3-50/5-3P SWITCH DISCONNECTOR FUSE XRG3-50/5-3P

FEATURES

- Easy, pre-engineered wire-free installation
- Simple removal and replace with plug-in contacts
- Fuse monitoring functionality (EFM)
- Up to 35% lower power losses
- Complies to standard IEC 60947-3



General Information	
Brand	ABB
Product Type	Fuse Disconnector
Suitable For	NH3
Туре	Main Switch

Technical Attributes	
Main Circuit Electrical Connection	Bolt Connection
Maximum Operational Voltage AC (V)	690
No. of Poles	3
Position of Control Element	Front Side
Power Dissipation at In (W)	240
Rated Conditional Short-Circuit Current - Inc (kA)	120
Rated Current (A)	630
Rated Uninterrupted Current - Iu (A)	630
Rated Voltage AC (V)	690

Physical Attributes	
Cable Entry	Side
Mounting Type	Busbar Mount

Dimensions



Fixing Centres (mm)	50
Fuse Size	NH3
Thickness (mm)	5
Weight (kg)	15.51

Protection & Standards	
Degree of Protection	IP41
Standards and Approvals	IEC 60947-3

Resources	
Product catalogue (Flipbook)	Download from here