

## Product No: ISDA068124R1

ABB XT 4N 160 EKIP LS/I IN=100A 3P F F ISDA068124R1

### FEATURES

- Fixed Three Pole
- Front Terminals
- Solid-state release
- ABB EcoSolutions



### General Information

Brand	ABB
Product Type	MCCB

### Technical Attributes

Design of Control Element	Toggle
Breaking Capacity 415V AC - I <sub>cu</sub> (kA)	36
L (0.4 to 1 x I <sub>n</sub> ) - I <sub>l</sub> (A)	40 - 100
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Front Side
No. of Poles	3
Overload Release Current Setting (A)	40
Power Loss (W)	3.5
Rated Current (A)	100
Rated Instantaneous Short-Circuit Current - I <sub>i</sub> (A)	100
Rated Uninterrupted Current - I <sub>u</sub> (A)	160
Rated Voltage (V)	690
S/I (1 to 10 x I <sub>n</sub> ) - I <sub>2</sub> /I <sub>3</sub> (A)	100 - 1000
Trip Unit	Ekip DIP LS/I

### Dimensions

Size of Frame	XT4
---------------	-----

## Protection & Standards

Degree of Protection

IP20

## Resources

Product catalogue (Flipbook)

[Download from here](#)