

Product No: 942 132-008

HIRSHMANN SPIDER III STANDARD LINE, 4X 10/100 BASE TX, RJ45 & 1X 100 BASE FX MULTIMODE ST, 12-24 VDC 942132008

FEATURES

- Fanless design
- Store and forward switching mode
- 10/100 Mbit/s Ethernet



General Information

Brand	HIRSHMANN
Product Type	Unmanaged
Series	SPIDER III

Technical Attributes

Connector Type	FX Port - ST
Current Consumption (mA)	100 at 24VDC
No. of 100Mb Ports	1
No. of Ethernet Ports	4
No. of Ports	4 x 10/100BASE-TX RJ45, 1 x 100BASE-FX
Nominal Power (W)	2.4
Power Consumption (W)	2.4
Rated Maximum Operational Voltage DC (V)	32
Rated Minimum Operational Voltage DC (V)	9.6
Rated Operational Voltage DC (V)	12 - 24
Switch Type	Switch - Unmanaged

Physical Attributes

Cable Type	FX Cable - Multi Mode
Maximum Temperature (°C)	60
Minimum Temperature (°C)	0
Mounting Type	DIN Rail / Wall

Operational Temperature Range (°C)	0 to +60
------------------------------------	----------

Dimensions

Dimensions (mm)	102H x 26W x 79D
-----------------	------------------

Protection & Standards

Degree of Protection	IP30
----------------------	------

Standards and Approvals	CE, FCC, EN61131, cUL61010-1/61010-2-201
-------------------------	--

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
