

Product No: DRM2P75FM

DEHN DEHNRail M FM SURGE ARRESTER DRM2P75FM

FEATURES

- Modular and pluggable two-pole
- Width: 1 module
- Fault indication
- With remote signalling contact
- Type 3 SPD according to EN 61643-11
- Energy-coordinated according to IEC 62305-4



General Information

Article No.	953208
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	Final Sub Circuit
Maximum Continuous Operating Voltage MCOV AC (V)	75
Maximum Continuous Operating Voltage MCOV DC (V)	75
No. of Poles	2P+PE
Nominal Discharge Current (8/20 μ s) - I _n (kA)	2
Nominal Load Current AC - I _n (A)	25
Nominal Voltage AC (V)	60
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 25 (L-N)/ ≤ 100 (L/N-PE)
Short-Circuit Withstand Capability - I _{sc} (kArms)	6
Signal C/O Contact	Yes
SPD Type	Type 3
Total Discharge Current (8/20 μ s) - I _{total} (kA)	4

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	0.08W x 0.11L x 0.02D
No. of Modules	1
Weight (kg)	0.09

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------