

Product No: 68581788

ABB ACS150 1.5KW 4.1A IP20 MICRO DRIVE ACS150-03E-04A1-4

FEATURES

- - Power range 0.37 to 4 kW/0.5 to 5 Hp
- - IP20 enclosure
- - Scalar control
- - Integrated user interface and potentiometer
- - Built-in brake chopper, EMC filter for second environment
- - Coated boards
- - Pre-defined connection macros



General Information

| | |
|---------------|-------------------|
| Brand | ABB |
| Product Type | Micro |
| Reference No. | ACS150-03E-04A1-4 |
| Series | ACS150 |

Technical Attributes

| | |
|----------------------------------|-----------|
| No. of Analogue Inputs | 1 |
| No. of Digital Inputs | 5 |
| No. of Phases | 3 |
| No. of Relay Outputs | 1 |
| Output Current - Light Duty (A) | 4.1 |
| Output Current - Normal Duty (A) | 4.1 |
| Output Power - Light Duty (kW) | 1.5 |
| Output Power - Normal Duty (kW) | 1.5 |
| Rated Supply Voltage AC (V) | 380 - 480 |

Physical Attributes

| | |
|--------------------------------|------------------------------|
| Ambient Temperature Range (°C) | -10 to 40 (No frost allowed) |
| Mounting Type | Cabinet |

Dimensions

| | |
|-----------------|-------------------|
| Dimensions (mm) | 239H x 70W x 142D |
|-----------------|-------------------|

| | |
|---------------|----|
| Size of Frame | R1 |
|---------------|----|

Protection & Standards

| | |
|----------------------|------|
| Degree of Protection | IP20 |
|----------------------|------|

| | |
|-------------------------|--------------------------------|
| Standards and Approvals | UL, cUL, CE, RCM, RoHS and EAC |
|-------------------------|--------------------------------|

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|