

Product No: LC36P2X18-65

IDE LOAD CENTRE IP65 2 X 18 MOD TRANSPARENT LID RAL7035 WITH E+N BARS LC36P2X18-65

FEATURES

- Sealable watertight distribution box
- Grey (RAL 7035) colour
- Transparent window
- Maximum operating temperature: -25°C to 40°C
- Maximum operating voltage: 1000V AC / 1500V DC
- IP65 Degree of Protection



General Information

| | |
|--------------|-------------------------|
| Brand | IDE |
| Product Type | Polycarbonate Enclosure |

Technical Attributes

| | |
|------------------------------------|------------------------------|
| Ball Pressure Test (°C) | 70 |
| Class of Insulation | Class II (Double Insulation) |
| Glow Wire Resistance (°C) | 650 |
| Maximum Operational Voltage AC (V) | 1000 |
| Maximum Operational Voltage DC (V) | 1500 |
| Rated Current (A) | 125 |

Physical Attributes

| | |
|--------------------------------|--|
| Ambient Temperature Range (°C) | -25°C to 40°C |
| Cable Entry | Top: 12 x M20 - 6 x M25 - 2 x M32 - 1 x M40 Bottom: 12 x M20 - 6 x M25 - 2 x M32 - 1 x M40 Int.: 4 x M25 Oblong Rear: 2 x OB 25/32/25 |
| Colour | RAL 7035 |
| Lid Material | Tinted PC, UV Protection |
| Material | Halogen-free Plastic |
| Mounting Type | Surface Mount |
| Window Type | Transparent |

Dimensions

| | |
|-----------------|----------------------|
| Dimensions (mm) | 418W x 436H x 148D |
| No. of Modules | 2 x 18 (36) DIN Rail |
| Weight (kg) | 3.07 |

Protection & Standards

| | |
|-------------------------|---|
| Degree of Protection | IP65 |
| Rated Impact Resistance | IK08 |
| Standards and Approvals | IEC 62208, Directive 2014/35/EU AS/NZS 61439.3:2016 Appendix ZZ Clauses 10.101 and 10.102 AS/NZS 3000 Clause 2.10.4.2, IEC 62208 Directive 2014 35/EU Compliant |

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|

DIMENSIONS

