


Product No: 943 662-003

HIRSCHMANN 24V DC DIN RAIL POWER SUPPLY UNIT 943662003

FEATURES

- 25 V DC DIN rail power supply unit
- Power supply units can be connected in parallel
- 24 months of guarantee period



General Information

Brand	HIRSCHMANN
Product Type	Power Supply Unit
Series	RPS
Software Diagnostics	LED (power, DC ON)

Technical Attributes

Current Consumption (mA)	0.35(max) at 296V AC
Electromagnetic Capability	10 V/m (80 MHz ... 2700 MHz)
Electrostatic Discharge (kV)	± 4 kV Contact Discharge; ± 8 kV Air Discharge
Input Voltage AC (V)	100-240
Input Voltage DC (V)	85-375
Maximum Nominal Output Voltage DC (V)	24
Operating Voltage Range	230V
Output Current (A)	1.3 at 10 -240V AC
Output Voltage DC (V)	24 V DC (±0.5%)
Rated Maximum Operational Voltage AC (V)	240
Rated Minimum Operational Voltage AC (V)	100
Rated Operational Voltage (V)	230
Resistance to Vibrations	Operating: 2 ... 500Hz 0,5m ² /s ³
Surge Voltage (kV)	Power Lines: 2 kV (Line/Earth), 1 kV (Line/Line)
Transition Type	2 kV Power Line

Physical Attributes

Maximum Temperature (°C)	70
Minimum Temperature (°C)	-10
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-10 - 70
Relative Humidity	5-95 %
Storage Temperature Range (°C)	-40 - 85

Dimensions

Dimensions (mm)	45W x 75H x 91D
Weight (g)	230
Weight (kg)	0.23

Protection & Standards

Degree of Protection	IP20
Standards	CE

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------