

Product No: SDD3-100-275-A

NOVARIS SURGE DIVERTER, DINSAFE, 100KA, 275VAC SDD3-100-275-A

FEATURES

- - DINsafe Surge Diverter
- - All Mode Protection
- - Thermal Sensing
- - LED Status Active Display
- - Safe Metal Enclosure
- - For DBs or for point of entry protection



General Information

Brand	NOVARIS
Product Type	Surge Protection Device
Series	SDD3

Technical Attributes

Connection Type	Shunt
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	12.5 (L-N)
Maximum Continuous Operating Voltage MCOV AC (V)	275 (L-N), 260 (N-PE)
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	100 (L-N), 60 (N-PE)
No. of Phases	3
No. of Poles	3P+N+PE
Nominal Discharge Current (8/20 μ s) - I _n (kA)	40 (L-N), 50 (N-PE)
Nominal Voltage AC (V)	230
Voltage Protection Level (3kA 8/20 μ s) - U _p (kV)	<0.8 (L-N), <1.2 (N-PE)
Voltage Protection Level - U _p (kV)	1.4 (L-N)

Physical Attributes

Mounting Type	DIN rail
Operational Temperature Range (°C)	-40 to 70

Dimensions

Dimensions (mm)	72W x 70H x 95L
-----------------	-----------------

Weight (g)	600
------------	-----

Protection & Standards

Degree of Protection	IP20
----------------------	------

Standards and Approvals	IEC 61643-11, AS/NZS 1768, UL 1449, IEEE 62.41.2
-------------------------	--

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------

TECHNICAL DRAWING

